

400HD IP Phone Series for Microsoft Teams

The **AudioCodes 400HD** series of native Microsoft Teams certified IP phones simplifies communications and boosts productivity with high voice quality, intuitive controls and ease-of-use. Built on AudioCodes' three decades of VoIP expertise, the 400HD portfolio supports all personas and use cases, with a unique combination of responsive touch screens and hard keys to ensure smooth, reliable operation in any working environment.

Designed for seamless Microsoft Teams integration, each device delivers crystal-clear audio, sharp displays, calendar synchronization and one-touch meeting join. The 400HD series can be centrally managed with **AudioCodes Device Manager**, enabling fast deployment, proactive monitoring and efficient issue resolution – reducing IT effort while improving user experience and productivity.

Microsoft Teams Feature Set

- Advanced Teams meetings integration (one-click join for Teams meetings; meeting call controls [Mute/Unmute, Hold/Resume, Hang Up, Add/Remove Participant]; meeting details)
- Calendar and presence (C455HD, C456HD, C470HD: calendar access and meeting details; presence integration; Exchange calendar integration; contact picture integration; corporate directory access)
- Basic and advanced calling features, including PSTN calling, visual voice mail and 911 support, P2P calls, in-call controls (Mute/Unmute, Hold, Transfer, End Call)
- Secure authentication sign-in (sign in with user credentials; sign in using PC/smartphone)
- Phone lock/unlock
- Dedicated 'Home', 'Calls', 'Calendar', 'People' and 'Voicemail' tabs for easy end-user access to a variety of features
- Dedicated Smart button (C430HD, C435HD, C436HD, C455HD, C456HD)
- Dedicated Home button (C470HD)
- Integrated sidecar (C436HD) and full touch sidecar (C455HD-DBW, C456HD)

C470HD IP Phone

The **C470HD** IP phone is a compact, all-purpose, Microsoft Teams-native business phone with large, portrait touchscreen and dedicated, one-touch function keys.

- Total Touch single surface design (touch screen, touch keys)
- High-end portrait 5.5" touch screen (720 X 1280), easily readable from a distance
- Full duplex speakerphone and headset connectivity
- Dual GbE support
- PoE or external power supply
- USB headset support
- Integrated dual band Wi-Fi connectivity*
- Android OS 12
- Kensington lock



C456HD IP Phone

The **C456HD** IP phone is a native Microsoft Teams desk phone built on MDEP and Android OS 13 to provide robust security and simplified, enterprise-grade management. Featuring a 5" color touch screen and a dedicated emergency call button, it is ideal for use in any workspace. An optional multi-purpose expansion module with 5" color touch screen is available for enhanced productivity.

- Full duplex speakerphone and headset connectivity
- Graphical 5" color TFT touch screen (1280 x 720) with multi-lingual support
- Optional multi-function expansion module with a vertical 5" color touch screen (480 x 854), supporting up to 60 one-touch speed dial contacts, plus call transfer, consult transfer, shared lines and queuing
- Dual GbE support
- PoE or external power supply
- USB headset support (USB-C port and in package Type-C to Type-A converter)
- Integrated dual band Wi-Fi 6 connectivity*
- Android OS 13 MDEP
- Kensington lock



C455HD IP Phone

The **C455HD** IP phone is a high-end, native Microsoft Teams executive IP phone with a large, color 5" touch screen. The C455HD-DBW model supports an optional dedicated color 5" touch screen expansion module.

- Full duplex speakerphone and headset connectivity
- Graphical 5" color TFT touch screen (1280 x 720) with multi-lingual support
- Vertical optional 5" color touch screen (480 x 854) expansion module for enhanced productivity, accommodating up to 50 contacts with one-click speed dial (C455HD-DBW)
- Dual GbE support
- PoE or external power supply
- USB headset support
- Integrated dual band Wi-Fi connectivity*
- Android OS 12
- Kensington lock



C436HD IP Phone

The **C436HD** native Microsoft Teams IP phone is a low-cost entry level/common area phone with a 4.3" color LCD screen, integrated sidecar and a dedicated Smart button, and is an excellent choice for retail environments looking for reliable, user-friendly solutions.

- Full duplex speakerphone and headset connectivity
- Main LCD 4.3" color landscape
- Integrated portrait sidecar (376 x 60) for contacts and dedicated speed dial keys with presence indication (Green/Red/Yellow)
- Dual GbE support
- PoE or external power supply
- USB and RJ-9 headset support
- Integrated dual band Wi-Fi 6 connectivity*
- Android OS OS12
- Kensington lock



C435HD IP Phone

The **C435HD** native Microsoft Teams IP phone is a low-cost entry level/common area phone, featuring a 4.3" color LCD screen and a dedicated Smart button.

- Full duplex speakerphone and headset connectivity
- 4.3" color LCD screen
- Dual GbE support
- PoE or external power supply
- USB and RJ-9 headset support
- Android OS 12
- Kensington lock



C430HD IP Phone

The **C430HD** native Microsoft Teams IP phone is a low-cost entry level/common area phone, featuring a 4.3" color LCD screen and a dedicated Smart button.

- Full duplex speakerphone and headset connectivity
- 4.3" color LCD screen
- Dual GbE support
- PoE or external power supply
- USB headset support
- Android OS 12
- Kensington lock





User Interface

- Intuitive and ergonomic design
- Virtual keyboard
- Multi-language support
- C470HD: Touch keys with backlight for Home, Mute, Speaker and Headset
- C470HD: Touch keys without backlight for Back, Hold, Transfer and Volume
- All other models: Mechanical keys with backlight for Mute, Speaker and Headset
- All other models: Mechanical keys without backlight for Transfer, Hold, Redial, Contacts, Back, 4-way navigation with OK
- Keypad (for C470HD the keypad is virtual, triggered via the speaker or headset touch key)
- Dedicated presence indication LED (Red/Green/Yellow)
- Multi-lingual UI support



Media Processing

- Voice coders: G.711, G.729, G.722, SILK
- Acoustic echo cancelation
- Adaptive jitter buffer
- Voice activity detection
- Comfort Noise Generation
- Packet lost concealment
- RTP/RTCP packetization (RFC 3550, 3551), SRTP (RFC 3711)



Network and Security Features

- HTTP/HTTPS secured provisioning
- UDP/TCP, NTP, DNS/SRV
- RTP/RTCP packetization (RFC 3550, RFC 3551), SRTP (RFC 3711)
- TLS version 1.2 – secured transport layer
- 802.1x for secured network access
- VLAN discovery modes: CDP-LLDP, CDP only or LLDP only
- Support for HTTP proxy and PAC file, either manually or via DHCP option 252



General Specifications (Common to All Models)

- TAA compliant
- Centralized management supported by the AudioCodes Device Manager and Microsoft Teams Admin Center
- Zero-touch provisioning with AudioCodes Redirect server
- AudioCodes SIP application for emergency calling upon losing connectivity to Microsoft Teams (requires an AudioCodes SBC and WebRTC license – contact AudioCodes for more details)

Unique Hardware Parameters

	C430HD	C435HD	C436HD	C455HD	C456HD	C470HD
Wired Connectivity	RJ-9 handset, USB headset Two RJ-45 Gigabit Ethernet (GbE) (10/100/1000BaseT Ethernet) ports for WAN and LAN	RJ-9 handset, RJ-9 headset and USB headset Two RJ-45 Gigabit Ethernet (GbE) (10/100/1000BaseT Ethernet) ports for WAN and LAN	RJ-9 handset, RJ-9 headset and USB headset Two RJ-45 Gigabit Ethernet (GbE) (10/100/1000BaseT Ethernet) ports for WAN and LAN	RJ-9 handset, USB headset Two RJ-45 Gigabit Ethernet (GbE) (10/100/1000BaseT Ethernet) ports for WAN and LAN	RJ-9 handset, USB headset Two RJ-45 Gigabit Ethernet (GbE) (10/100/1000BaseT Ethernet) ports for WAN and LAN	RJ-9 handset, USB headset Two RJ-45 Gigabit Ethernet (GbE) (10/100/1000BaseT Ethernet) ports for WAN and LAN
Screen Orientation	Landscape	Landscape	Main LCD 4.3" color landscape Integrated sidemar monochrome LCD (376 x 60) portrait	Landscape	Landscape	Portrait
Wi-Fi	N/A	N/A	C436HD "DBW" CPN Dual band 2.4GHz and 5GHz 802.11a/b/g/n/ac/ax WiFi support	C455HD "DBW" CPN Dual band 2.4GHz and 5GHz 802.11a/b/g/n/ac Wi-Fi support	Dual band 2.4GHz and 5GHz 802.11a/b/g/n/ac/ax Wi-Fi 6 support	C470HD "DBW" CPN Dual band 2.4GHz and 5GHz 802.11a/b/g/n/ac Wi-Fi support
PoE Class	2 (IEEE802.3af)	3 (IEEE802.3af)	3 (IEEE802.3af)	3 (IEEE802.3af)	3 (IEEE802.3af)	3 (IEEE802.3af)
DC Power Jack	12V, optional external power supply 2A/12V 100-240V	12V, optional external power supply 2A/12V 100-240V	12V, optional external power supply 2A/12V 100-240V	12V, optional external power supply 2A/12V 100-240V	12V, optional external power supply 2A/12V 100-240V	12V, optional external power supply 2A/12V 100-240V
In-box base stand	Yes Single position	Yes Single position	Yes Single position	Yes Two positions	Yes Single position	No
In-box wall mount	No	Yes****	Yes****	Yes	No	No
USA type wall mount kit (purchased separately)	Yes	Yes	Yes	No	Yes (main unit only without expansion)	No
Unit Dimensions (mm)	212.2(W)×210.4(D)×90.93(H) 212.2(W)×210.4(D)×177.91(H)	249(W)×132(D)×189.2(H) 249(W)×168(D)×160.9(H)	249(W)×132(D)×189.2(H) 249(W)×168(D)×160.9(H)	C455HD 236(W)×195(D)×195.7(H) 236(W)×200(D)×165.9(H) C455HD with Expansion Module*** 321.5(W)×195(D)×195.7(H) 321.5(W)×200(D)×165.9(H)	C456HD 225.9(W)×210.35(D)×92.6(H) 225.9(W)×193.8(D)×178.6(H) Expansion Module 119.7(W)×209.4(D)×49.4(H)	180(W)×165(D)×230(H)
Unit Weight (kg)	1.018	0.916	0.934	C455HD 1.014/0.988 C455HD with Expansion Module*** 1.311/1.285	C456HD 1.114 Expansion Module 0.310	Regular 1.165 Triangular 1.200
Unit Box Weight (Gross) (kg)	1.508	1.388	0.94	C455HD 1.620/1.548	C456HD 1.505 Expansion Module 0.714	Regular 1.741 Triangular 1.784
Unit Box Dimension (mm)	320(W)×244(D)×90(H)	316(W)×255(D)×95(H)	316(W)×255(D)×95(H)	C455HD 280(W)×245(D)×110(H)	C456HD 323(W)×238(D)×86(H) Expansion Module 320(W)×175(D)×76(H)	Regular 238(W)×275(D)×174(H) Triangular 240(W)×347(D)×231(H)
Master Carton Dimension (mm)	510(W)×466(D)×362(H)	532(W)×500(D)×361(H)	532(W)×500(D)×361(H)	C455HD 579(W)×467(D)×291(H)	C456HD 508(W)×466(D)×363(H) Expansion Module 416(W)×378(D)×362(H)	Regular 490(W)×540(D)×308(H) Triangular 380(W)×500(D)×272(H)
Master Carton Weight (kg)	16.820	15.9	15.95	C455HD 15.1/14.5	C456HD 16.530 Expansion Module 8.202	Regular 12.35 Triangular 8.258
Storage/ Operation Temperature	(-)20° to +70°C / 0° to +40°C [(-) 4 to +158°F / 32 to +104°F]	(-)20° to +70°C / 0° to +40°C [(-) 4 to +158°F / 32 to +104°F]	(-)20° to +70°C / 0° to +40°C [(-) 4 to +158°F / 32 to +104°F]	(-)20° to +70°C / 0° to +40°C [(-) 4 to +158°F / 32 to +104°F]	(-)20° to +70°C / 0° to +40°C [(-) 4 to +158°F / 32 to +104°F]	(-)20° to +70°C / 0° to +40°C [(-) 4 to +158°F / 32 to +104°F]
Homologation and Approvals**	cTUVus (UL 62368-1), CB (IEC 62368-1:2014), EN55032 Class B, EN61000-3-2, EN61000-3-3 CE mark, EMC, ICES-003 Issue 7	cTUVus (UL 62368-1), CB (IEC 62368-1:2014), EN55032 Class B, EN61000-3-2, EN61000-3-3 CE mark, EMC, ICES-003 Issue 7	EMC part ICES-003 Class B, EN55032: 2015 +A11:2020, EN50035:2017 +A11:2020, EN61000-3-2, EN61000-3-3, EN301489-1, EN301489-3, EN301489-17, Safety part IEC/EN/UL62368-1:2014, Radio part EN300328, EN301893, EN300440, EN62311	FCC part 68.316, 317 HAC, ICES-003 Class B, EN55032 Class B, EN61000-3-2, EN61000-3-3, UL-62368-1, IEC-, CE mark, cTUVus. For Models with Bluetooth and Wi-Fi, FCC part 15.247, FCC part 15.407, EN300328, EN300440, EN301893, EN301489.	FCC part 68.316, 317 HAC, ICES-003 Class B, EN55032 Class B, EN61000-3-2, EN61000-3-3, UL-62368-1, IEC-, CE mark, cTUVus. For Models with Bluetooth and Wi-Fi, FCC part 15.247, FCC part 15.407, EN300328, EN300440, EN301893, EN301489.	FCC part 68.316, 317 HAC, ICES-003 Class B, EN55032 Class B, EN61000-3-2, EN61000-3-3, UL-62368-1, IEC-, CE mark, cTUVus. For Models with Bluetooth and Wi-Fi, FCC part 15.247, FCC part 15.407, EN300328, EN300440, EN301893, EN301489.

* Wi-Fi is supported in specific regions such as the USA, Canada, the European Union, Switzerland, Israel and others, and requires a specific CPN with a "DBW" suffix when ordering. For an updated list of supported regions and countries, please contact an AudioCodes representative.

** The homologation list can change from model to model. Please contact AudioCodes for up to date model specific information.

*** The expansion module is supported for the C455HD-DBW only. **** Same base stand with different assembly used for wall mount.

International Headquarters
Naimi Park, 6 Ofra Haza Street, Or Yehuda, Israel
Tel: +972-3-976-4000

AudioCodes Inc.
80 Kingsbridge Road Piscataway, NJ 08854
Tel: +1-732-469-0880

www.audiocodes.com/contact
www.audiocodes.com

©2026 AudioCodes Ltd. All rights reserved. AudioCodes, AC, HD VoIP, HD VoIP Sounds Better, IPmedia, Mediant, MediaPack, What's Inside Matters, OSN, SmartTAP, User Management Pack, VMAS, VoiPerfect, VoiPerfectHD, Your Gateway to VoIP, 3GX, AudioCodes One Voice, AudioCodes Meeting Insights, and AudioCodes Room Experience are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners. Product specifications are subject to change without notice.

